

I hereby certify that this paper is being deposited with the United States Postal Service as Express Mail in an envelope addressed to: BOX PATENT APPLICATION, ASSISTANT COMMISSIONER FOR PATENTS, Washington, D.C. 20231, on this date.

January 11, 2002

Date

Express Mail No EL846174092US

Dail Lano

1 Inventors: Eric DeLano

2 CUSTOMIZED PORTS IN A CROSSBAR AND
3 METHOD FOR TRANSMITTING DATA BETWEEN
4 CUSTOMIZED PORTS AND SYSTEM AGENTS

5 [0001] The present invention generally relates to customized ports
6 in a crossbar. More specifically, it relates to customized ports in a crossbar
7 and a method for transmitting data on the customized ports in a crossbar.

8 [0002] A crossbar is a chip or chip component commonly used to
9 provide a processing system of high frequency links between multiple ports
10 and system agents. Generally, each port is designed as an input port for
11 receiving data from system agents (i.e., source agents) and an output port
12 for transmitting data from the input ports to other system agents (i.e.,
13 destination agents). The system agents can include multiple computer
14 components, such as a central processing unit (CPU), Input/Output (I/O)
15 controllers, memory controllers and cache memory.

1 [0003] More particularly, the requesting agents are generally the
2 CPUs, which can demand different amounts of data depending on the
3 particular requests. The responding agents are generally the Input/Output
4 (I/O) controllers, memory controllers and cache memory, which are also
5 defined by various configurations and bandwidth requirements. As a result
6 of the various agents and the multiple ports, a crossbar is used to sort out
7 the high-frequency links to meet the demands of these competing system
8 agents for multiple ports, which may comprise thousands of different ports.
9 To further the complexity of the processing system, each of the ports are
10 generally divided into multiple virtual communication channels in order to
11 fully utilize the potential of each port.

12 [0004] The ports in a crossbar typically have the same fixed
13 bandwidth for transmission. The problem with a typical crossbar
14 configuration is that it does not effectively deal with the demands of
15 different bandwidth needs for the requesting and responding agents. For
16 example, a requesting agent may require only a fraction of the fixed
17 bandwidth for a particular transmission. Nevertheless, the full fixed
18 bandwidth is used, since all ports in a typical crossbar have the same fixed
19 bandwidth. As a result, bandwidth is wasted in the process. On the other
20 hand, if there is not enough fixed bandwidth designed into the crossbar,
21 performance will also suffer. Furthermore, multiple processors have been
22 used within a single computer, which requires more flexibility in dealing
23 with the different available bandwidth needs. Thus, there is a need for an
24 improved crossbar and method for transmitting data between various
25 system agents and ports.

BRIEF SUMMARY OF THE INVENTION

[0005] The present invention is directed to customized ports in a crossbar. More specifically, it relates to customized ports in a crossbar and a method for transmitting data on the customized ports in a crossbar.

[0006] The present invention provides a crossbar for providing connections between a plurality of ports and a plurality of system agents via a processing system, which includes a plurality of ports, with each port being capable of being an input port customized for receiving data from a source agent and an output port customized for transferring data to a destination agent, and crossbar control data for specifying crossbar control information for transferring data from an input port to an output port having different port configurations.

[0007] The present invention also provides a method for transmitting data between customized ports and a plurality of system agents in a processing system via a crossbar, which includes the steps of receiving data on an input port, obtaining the destination output port for the data received on the input port, determining whether the input port has the same configurations as the output port, obtaining control information from the crossbar control data when the input port does not have the same configurations as the output port, processing the data according to the obtained control information from the crossbar control data, and transmitting the processed data to the destination output port.

DESCRIPTION OF THE DRAWINGS

[0008] FIGURE 1 is a schematic diagram of a simplified prior art crossbar;

- 1
- 2
- 3
- 4
- 5
- 6
- 7
- 8

3
45
67
8

9

10
11
12
13
14
15
16
17
18
19
20
21
22

23
24
25

Each port is typically designed as an input port for receiving data from a source agent and an output port for transmitting data from the input port to a destination agent. In particular, as shown in FIG. 1, port0 12 is designed for an input port 20 with an 8 bit data width and an output port 22 with also an 8 bit data width. In other words, an 8 bit length data width is allowed for transmission on port0 12 as input data or output data. Generally, if a connection via the crossbar is N bit wide and operates at a bandwidth of X bit per second, M bit of data will complete a transmission in $M/(N*X)$ seconds. Data received on the input ports typically includes control data 24, which indicates information and/or destination output port relating to the data.

[0015] The crossbar, in turn, uses the control information from the control data 24 to negotiate a connection with one of the ports. The crossbar typically uses the control information to verify the validity of port information relating to the data and to obtain the requested destination output port. In this case, a 1 bit length to validate the request, and a 2 bit length to specify the destination port. Control data is well-known in the art, and they vary in bit length and are generally sent from the source agent along with the data received on the input port. A typical crossbar is designed to have the same bandwidth for the input and the output of each port. Thus, every port in the crossbar typically has the same bit length implementation.

[0016] In the exemplary prior art crossbar shown in FIG. 1, port1 14 is similarly designed as an 8 bit input port 26 and output port 28 with a 3 bit length for control data 30 to validate the input data and provide a destination port for the input data. Port2 16 is designed as an 8 bit input

1 port 32 and output port 34 with a 3 bit length for control data 36. Similarly,
2 as shown, port3 18 is also an 8 bit input port 38 and output port 40 with a 3
3 bit length for control data 42. Although the length of the data bit and
4 control bit may vary in conventional crossbars, the ports of the crossbars are
5 all generally set up to have identical input and output port configurations
6 across all the ports.

7 [0017] An embodiment of a crossbar designed in accordance with
8 the principles of the present invention is shown in FIG. 2, and indicated
9 generally at 50. For clarification, only 4 ports are shown for the crossbar,
10 specifically port0 52, port1 54, port2 56 and portN 58. As indicated by
11 portN 58, the crossbar can be implemented with as many ports as desired,
12 and the only limitation is the hardware of the computing system. Thus,
13 other implementations of any number of ports for the present crossbar are
14 contemplated and are within the scope of the present invention.

15 [0018] As shown, unlike the prior art, each port of the present
16 crossbar can be customized with different port configurations. In particular,
17 input port0 60 and the output port0 62 of port0 52 are customized to receive
18 "A" data bits and transmit "B" data bits, which indicates different bit
19 lengths for the input port and the output port. Control data 64 generally
20 sent together with data received on the input port0 60 will have "C1" bits.
21 The present invention also includes crossbar control data 66 having "C2"
22 bits that indicates crossbar control information for transferring data from the
23 input port0 62 to an output port0 62 having different port configurations.

24 [0019] The crossbar control data is internal data from the
25 crossbar, which is generated at the time of the design of the crossbar.
26 Unlike the control data 64, the crossbar control data 66 is not sent from the

1 source agents. Rather, the computer engineer provides the crossbar control
2 data at the time when the crossbar with customized ports is created. Thus,
3 the crossbar control data 66 is preferably implemented with the crossbar. In
4 order for the ports with different configurations to work in unison, the
5 crossbar control data 66 is placed internally so that the received data can be
6 correctly formatted for transmission to a port with different configurations
7 (e.g., bandwidth). As a result, even a single port can be customized as an
8 input port and an output port with different port configurations.

9 [0020] The customization and variations of the port
10 configurations can be extended throughout other ports in the crossbar. As
11 shown, port1 54, port2 56 and portN 58 all contain different width
12 configurations. More specifically, port1 54 is customized as a "D" bit
13 width input port 68 and a "E" bit width output port 70 with a "F1" bit width
14 for control data 72 and a "F2" bit width for crossbar control data 74.
15 Similarly, port2 56 is customized as a "G" bit width input port 76 and a "H"
16 bit width output port 78 with a "I1" bit width for control data 80 and a "I2"
17 bit width for crossbar control data 82, and portN 58 is also customized as a
18 "J" bit width input port 84 and a "K" bit width output port 86 with a "L1"
19 bit width for control data 88 and a "L2" bit width for crossbar control data
20 90.

21 [0021] Although all the ports are shown to have different
22 bandwidth configurations, this is an extreme example to show the flexibility
23 of possible implementations for the present invention. However, in
24 practice, the ports will likely have far less variation, because the
25 implementation may be too complex for the needs of most current
26 processing systems. In addition, in this example, the crossbar control data

1 have been shown with different bandwidth data lengths, and they are
2 specific to the ports. Again, the example provided illustrates the many
3 possibilities and flexibility of the present invention. In practice, there is
4 likely one set of crossbar control data for the whole crossbar, containing
5 only a simple control algorithm.

6 **[0022]** It is also important to note that although width of the ports
7 is shown as the main port configuration that is customized, other port
8 configurations are contemplated as long as the crossbar control data can be
9 processed in the crossbar. For example, port configuration of frequency
10 may be implemented. Because of the hardware limitation of current chips,
11 width of the ports and bandwidth are generally the main configurations for
12 ports in a crossbar. However, as technology expands in the area,
13 customization of other port configurations may be more practical, and these
14 various implementations are within the scope of the present invention.

15 **[0023]** An overall view of the processing system implemented
16 with the present crossbar is shown in FIG. 3, and indicated generally at 100.
17 The preferred implementation includes one or more virtual channels (two of
18 which are shown) for each port for receiving data from a source agent (not
19 shown). In particular, input port0 60 includes virtual channels 102, 104,
20 input port1 68 includes virtual channels 106, 108, input port2 76 includes
21 virtual channels 110, 112 and input port3 84 includes virtual channels 114,
22 116. As shown, each virtual channel 102, 104, 106, 108, 110, 112, 114, 116
23 is implemented with a First-In-First-Out (FIFO) buffer respective
24 prioritizing devices 118, 120, 122, 124, 126, 128, 130, 132, respective
25 registers 134, 136, 138, 140, 142, 144, 146, 148, and respective
26 multiplexors ("MUXs") 150, 152, 154, 156, 158, 160, 162, 164.

[0024] The use of virtual channels, MUXs and registers is well established in the art of crossbars. Each input port is divided into multiple virtual channels for receiving data from multiple source agents. Although two virtual channels are shown in FIG. 3 for simplicity, it is typical for each port to be implemented with 5 or more virtual channels. Because each port with the assigned virtual channels is customized differently, a separate register for storing the data in a temporary memory and a MUX for switching configuration internal to the crossbar are preferably implemented for each virtual channel. Depending on the differences and design of the port configurations in the crossbar, an implementation with a fewer number of registers and MUXs may be possible and will be apparent to one skilled in the art.

[0025] Data received from the virtual channels are then transmitted to a requested destination output port. As shown, there are also separate MUXs 166, 168, 170, 172 that correspond to the output ports 62, 70, 78, 86, respectively, which are followed by a 4 to 1 MUX 174. The 4 to 1 MUX 174 then transmits the data to a register 176 of one of the destination output ports. Although only one output port is shown for simplicity (i.e., port1 70), there would be 4 output ports having 4 separate registers (one shown) that transmit the data to a destination output port, since the crossbar has 4 ports in the example shown in FIG. 2. As shown on each MUX 166, 168, 170, 172, the bandwidth for each output port (i.e., B-bit, E-bit, H-bit, K-bit) is different from the input ports (i.e., A-bit, D-bit, G-bit, J-bit). As a result, in order for data from the input port to be transmitted to the output port having a different port configuration, the data must be first processed using the control information from the crossbar control data.

1 [0026] Several implementations are contemplated for the
2 processing of data. The crossbar control data can be stored and processed at
3 several places in this example. The crossbar control data can be processed
4 by either the MUX 166, 168, 170, 172 or the 4 to 1 MUX 174 on the output
5 ports. Because of the configuration of the overall system shown in FIG. 3,
6 the crossbar control data are preferably implemented at the output ports 62,
7 70, 78, 86. However, other implementations at the input ports 60, 68, 76,
8 84 are also contemplated. For example, the crossbar control data can be
9 processed by either the registers (i.e., a shift register) 134, 136, 138, 140,
10 142, 144, 146, 148 or the MUXs 150, 152, 154, 156, 160, 162, 164 of the
11 virtual channels 102, 104, 106, 108, 110, 112, 114, 116. As noted, various
12 alternative implementations are contemplated, and they are within the scope
13 of the present invention.

14 [0027] Turning to an important aspect of the illustrated
15 embodiment of the present invention, a flow chart of the preferred
16 functionality of the illustrated embodiment of the present invention is
17 shown in FIG. 3, and indicated generally at 180. After receiving data with
18 the corresponding control data on an input port from a source agent (block
19 182), the control data of the received data are then read (block 184) and
20 determined whether the control data contain valid information for the data
21 received on the input port (block 186). If not, the process is aborted (block
22 188), since the control data contained invalid information. If, however, the
23 information from the control data has been verified as valid (block 186), the
24 requested destination output port for the received data is obtained from the
25 control data (block 188).

1 [0028] After the destination output port for the received data is
2 obtained from the control data (block 188), it is next determined whether
3 the input port that received the data has the same port configuration as the
4 obtained destination output port (block 190). If the input port has the same
5 configuration as the output port (block 190), the received data will be
6 transmitted to the destination output port (block 192). If, on the other hand,
7 the input port does not have the same configuration as the output port
8 (block 190), control information is then obtained from the crossbar control
9 data (block 194) for processing the received data to the configuration of the
10 output port (block 196). After the data is processed, the processed data is
11 then transmitted to the output port (block 198).

12 [0029] A flow chart illustrating the preferred functionality of the
13 processing step (block 196) shown in FIG. 4 will be explained in FIG. 5. It
14 should be noted that the processing method shown is for processing ports
15 with different width port configurations. However, the present invention
16 contemplates use with other port configurations, and other implementations
17 and methods relating to these port configurations are within the scope of the
18 present invention. Based on port configuration of different widths, the first
19 step in the processing method (block 196) is to determine whether the width
20 of the input port is greater than the width of the output port (block 200). If
21 not, the data are submitted as processed data (block 202) back to the method
22 shown in FIG. 4, since it is not necessary to format data with smaller length
23 bit that can be read by width with greater length bit. In other words, a 24
24 bit width port can read any data bits that are equal to or fewer than 24 bit
25 length, but not data that are more than 24 bit length.

1 [0030] However, if the width of the input port is more than the
2 width of the output port (block 200), modification to the data is necessary in
3 order to transmit the data to a port with less available width. Thus, the
4 width of the output port must be ascertained (block 204) in order to format
5 the data from the input port to data configured for the width of the output
6 port (block 206). The formatted data will be submitted as the processed
7 data. In practice, the data will be transmitted by shifting the data bits to the
8 width of the output port. For example, if a 24 bit width input port requests
9 to transmit data to an output port with an 8 bit width, the data will then be
10 shifted or divided into 8 bit for each transmission. Since there are 24 bits
11 total, the data will be transmitted 8 bits at a time until all 24 bits are sent.
12 This can be done either through the use of a MUX or a shift register.
13 Various methods can be used and they will be apparent to one skilled in the
14 art. However, it should be noted that these various other methods are
15 within the scope of the present invention.

16 [0031] From the foregoing description, it should be understood
17 that an improved system and method for providing connections between a
18 plurality of customized ports and a plurality of system agents have been
19 shown and described, which have many desirable attributes and advantages.
20 The system and method provide a way for ports in a crossbar to be
21 customized and defined according to the needs and implementations
22 selected by the engineers, creating a more flexible crossbar that is better
23 suited to meet the demands of the various utilization needs of the systems.

24 [0032] While various embodiments of the present invention have
25 been shown and described, it should be understood that other modifications,
26 substitutions and alternatives are apparent to one of ordinary skill in the art.

1 Such modifications, substitutions and alternatives can be made without
2 departing from the spirit and scope of the invention, which should be
3 determined from the appended claims.

4 [0033] Various features of the invention are set forth in the
5 appended claims.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221